


Konstruktioni čelik - crn

Prema EN 10025 / 10083 / 10084, Tolerancija prema DIN 1013, Dužina šipki ca. 6m

 dimenzija mm	W e r k s t o f f							
	1.0570	1.1181	1.1191	1.1221	1.6582	1.6587	1.7131	1.7225
	St 52.3 Č 0562	Ck 35 Č1431	Ck 45 Č1531	Ck 60 Č1731	34CrNiMo6V poboljšan	17CrNiMo6G žaren	16MnCr5G žaren	42CrMo4V Č4320 Č4732 poboljšan
	prirodno tvrd	prirodno tvrd	prirodno tvrd	prirodno tvrd				
Braon		Plava	Bijela	Boja označavanja Žuta		Violet/Žuta	Violet	Orange
16			●				●	
20	●		●	●	●		●	●
25	●		●	●	●		●	●
28							●	
30	●		●	●	●		●	●
32			●					
35	●		●	●	●		●	●
38			●					
40	●		●	●	●		●	●
42			●					
45	●		●	●	●		●	●
50	●		●	●	●	●	●	●
55	●		●	●	●		●	●
60	●	●	●	●	●	●	●	●
63							●	
65	●	●	●	●			●	●
70	●	●	●	●	●	●	●	●
75	●	●	●	●			●	●
80	●	●	●	●	●	●	●	●
85	●	●	●				●	●
90	●	●	●	●	●	●	●	●
95	●	●	●				●	●
100	●	●	●	●	●	●	●	●
105	●	●	●				●	●
110	●	●	●	●	●	●	●	●
115	●	●	●				●	●
120	●	●	●	●	●	●	●	●
125	●	●	●				●	●
130	●	●	●	●	●	●	●	●
135		●	●				●	
140	●	●	●	●	●	●	●	●
145		●	●				●	
150	●	●	●	●	●	●	●	●
160	●	●	●	●	●	●	●	●
170	●	●	●	●			●	●
175			●					
180	●	●	●		●	●	●	●
190	●	●	●				●	●
200	●				●	●	●	●
210	●						●	●
220	●					●	●	●
230	●						●	●
240	●							
250	●				●			
260	●							
300								●

Normalisierte Ausführungen finden Sie auf dem Blatt "Baustahl überdreht"!