



# Konstrukcioni čelik-crn flah

Prema EN 10025 / 10083 / 10084, Tolerancije prema DIN 1017, dužina šipki ca. 3-6m

 Dimension mm	W e r k s t o f f							
	1.0570 St 52.3 Č0562 prirodno tvrd	1.1181 Ck 35 Č1431 prirodno tvrd	1.1191 Ck 45 Č1531 prirodno tvrd	1.1221 Ck 60 Č1731 prirodno tvrd	1.6582 34CrNiMo6V poboljšan	1.6587 17CrNiMo6G žaren	1.7131 16MnCr5G žaren	1.7225 42CrMo4V poboljšaan
	Braon	Plav	Bijel	Žut	Orange/Bijel	Violet/Žut	Violet	Orange
40 x 10			●					
x 15			●					
x 20			●					
x 25			●					
x 30			●					
50 x 10			●					
x 15			●					
x 20			●					
x 25			●					
x 30			●					
x 40			●					
60 x 10			●					
x 15			●					
x 20			●					
x 25			●					
x 30			●					
x 40			●					
70 x 20			●					
x 25			●					
x 30			●					
x 40			●					
80 x 12			●					
x 15			●					
x 20			●					
x 25			●					
x 30			●					
x 40			●					
x 50			●					
90 x 20			●					
x 40			●					
x 50			●					
x 60			●					
100 x 20			●					
x 30			●					
x 40			●					
x 50			●					
x 60			●					
120 x 20			●					
x 30			●					
x 40			●					
x 50			●					
x 60			●					
150 x 20			●					
x 30			●					
x 40			●					
x 50			●					
150 x 60			●					

# Konstruktioni čelik-crn flah

Prema EN 10025 / 10083 / 10084, Tolerancije prema DIN 1017, dužina šipki ca. 3-6m

 Dimension mm	W e r k s t o f f							
	1.0570	1.1181	1.1191	1.1221	1.6582	1.6587	1.7131	1.7225
	St 52.3 Č0562 prirodno tvrd	Ck 35 Č1431 prirodno tvrd	Ck 45 Č1531 prirodno tvrd	Ck 60 Č1731 prirodno tvrd	34CrNiMo6V poboljšan	17CrNiMo6G žaren	16MnCr5G žaren	42CrMo4V poboljšaan
	Boja označavanja							
	Braon	Plav	Bijel	Žut	Orange/Bijel	Violet/Žut	Violet	Orange
200 x 20			●					
x 30			●					
x 40			●					
x 50			●					
x 60			●					